



LOVE & ASSOCIATES

MANUFACTURERS OF
INDUSTRIAL COATINGS

TECHNICAL
DATA SHEET

13 – SERIES NON-SKID

DESCRIPTION: 13 Series Non-Skid: A non-skid aggregate coating for use on various surfaces. Contains a special combination of aggregates to provide a non-skid surface during rough weather conditions and ongoing daily wear and tear.

TYPICAL USES INCLUDE

Storage Tanks and Piping
Machinery and Equipment

Structural Steel
Bridges-Railcar

Cranes and Lift Equipment
Buildings, Trucks and Trailers

TYPICAL PHYSICAL PROPERTIES:

COLOR:	Various
COMPONENTS:	One
GLOSS:	Low
VOC:	3.0 LBS/GAL
WT./GALLON:	12.51 - 13.50 +/- .2
POT LIFE:	N/A
VISCOSITY AT 77° F:	110 KU
SHELF LIFE:	3 Years
SOLIDS BY WEIGHT:	75.8%
TEMP. RESISTANCE:	225° F
SOLIDS BY VOLUME:	55%
CHEM. RESISTANCE:	Moderate
THEORETICAL COVERAGE:	150-200 ft ² /gal Rolling
FLASH POINT:	90° F, TCC

RECOMMENDED D.F.T.: 6-8 Dry mils

DRY TIME: @ 77° F, 55% R.H.

To Touch: 4 Hours
To Handle: 16-24 Hours
To Recoat: 24 Hours

THINNING: NOT NORMALLY REQUIRED

Brush: T-33 or Mineral Spirits

APPLICATION METHODS:

Brush, Roll

FILM THICKNESS:

Wet: 11-14 mils
Dry: 6-8 mils

CLEANING OF EQUIPMENT:

T-33/T-31 or Mineral Spirits/ VM&P Naphtha

**PACKAGING:**

1 Gallon Cans 5 Gallon Pails

APPLICATION CONDITIONS:

Surface should be dry, above 40° F and at least 5° F above the dew point.

SURFACE PREPARATION:

Remove all grease, oil, dirt, dust or other contaminants.

NORMAL SERVICE: SSPC-SP2 or 3 Hand or Power Tool Cleaning.

PREVIOUSLY PAINTED SURFACES:

Remove all grease, oil, dirt, dust or other contaminants. Surface must be clean and dry, SSPC-SP2 or 3 or SSPC-SP7.

SAFETY INFORMATION**DOT CLASSIFICATION: PAINT UN 1263**

DANGER: Causes eye burns and skin irritation. Vapor harmful. Dried film of this paint may be harmful if eaten or chewed. Contains organic solvent. Do not get in eyes, on skin or on clothing. Wear eye protective equipment when handling. Keep away from heat, sparks, and flame. Avoid breathing vapor or mist. Wash thoroughly after handling. Wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable level. Follow respirator manufacturer's directions for use. Keep container closed. Where products contain lead, do not use in dwellings or on surfaces accessible to children. Keep out of reach of children.

FIRST AID: IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. FOR SKIN CONTACT, FLUSH WITH WATER AND WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. IF INHALED, REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH, AND CALL A PHYSICIAN.

NOTICE: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or **fatal**.

FOR INDUSTRIAL USE ONLY.